

Type N F/F Bulkhead Coaxial RF Surge Protector, DC - 6GHz,  
90W, IP67, 60 V Max., 5mJ, 20kA, Gas Discharge Tube



## GT-NFF-AL

### Features

- Surge current of 20kA
- Max Power 90W(RMS)
- Frequency range from DC to 6 GHz
- N-type Female connectors
- Waterproof IP67 rated
- DC Pass
- VSWR <1.1:1 Typical
- CE & RoHS compliant
- Bidirectional

### Applications

- WiFi
- GPS
- Land mobile radio

### Description

RF surge protector (also known as lightning arrester or surge arrester) GT-NFF-AL from PolyPhaser, utilizing a gas tube (GT or GDT). This RF surge protector component is manufactured in a coaxial in-line design with wide operating frequency range. All PolyPhaser RF surge protector products are available in stock with same day shipping.

### Electrical Specifications

Surge Protector Type  
DC Handling

Gas Discharge Tube  
DC Pass

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		6	GHz
Impedance		50		Ohms
VSWR		1.1:1	1.2:1	
Insertion Loss		0.1	0.25	dB
Operating Voltage (DC)			60	Volts
Operating Current (DC)			10	A
Input Power, CW			90	Watts
90W @ 30MHz				
9W @ 3GHz				
Surge Current			20	kA
IEC 61000-4-5 8/20µs WAVEFORM				
Turn On Voltage		300		Volts
Throughput Energy			5	mJ

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications:  
[Type N F/F Bulkhead Coaxial RF Surge Protector, DC - 6GHz, 90W, IP67, 60 V Max., 5mJ, 20kA, Gas Discharge Tube GT-NFF-AL](#)

Type N F/F Bulkhead Coaxial RF Surge Protector, DC - 6GHz,  
90W, IP67, 60 V Max., 5mJ, 20kA, Gas Discharge Tube



## GT-NFF-AL

### Specifications by Frequency

Description	F1	F2	F3	F4	F5	Units
Frequency Range	DC to 3	3 to 4	4 to 6			GHz
VSWR, Typ	1.1:1	1.1:1	1.2:1			
Insertion Loss, Max	0.1	0.1	0.25			dB

### Mechanical Specifications

#### Size

Length	2.22 in [56.39 mm]
Width/Diameter	0.86 in [21.84 mm]
Weight	0.15 lbs [68.04 g]

#### Configuration

Input Connector	N Female
Output Connector	N Female

### Environmental Specifications

#### Temperature

Operating Range	-55 to +85 deg C
Ingress Protection (IP) Rating	IP67

### Compliance Certifications

RoHS  
CE

### Plotted and Other Data

Notes:


Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications:  
[Type N F/F Bulkhead Coaxial RF Surge Protector, DC - 6GHz, 90W, IP67, 60 V Max., 5mJ, 20kA, Gas Discharge Tube GT-NFF-AL](#)

Type N F/F Bulkhead Coaxial RF Surge Protector, DC - 6GHz,  
90W, IP67, 60 V Max., 5mJ, 20kA, Gas Discharge Tube



## GT-NFF-AL

### Typical Performance Data




Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications:  
[Type N F/F Bulkhead Coaxial RF Surge Protector, DC - 6GHz, 90W, IP67, 60 V Max., 5mJ, 20kA, Gas Discharge Tube GT-NFF-AL](#)

Type N F/F Bulkhead Coaxial RF Surge Protector, DC - 6GHz,  
90W, IP67, 60 V Max., 5mJ, 20kA, Gas Discharge Tube



## GT-NFF-AL



PolyPhaser protects and increases the reliability of global RF communications networks, including transportation, telecommunications, defense, security and industrial applications, with superior RF surge protection technologies including DC Block, DC Pass and Ultra Low PIM. Backed by responsive service and expert technical support PolyPhaser continually expands its product offering and services to serve engineers' urgent needs for RF components in mission critical communication networks.


Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Type N F/F Bulkhead Coaxial RF Surge Protector, DC - 6GHz, 90W, IP67, 60 V Max., 5mJ, 20kA, Gas Discharge Tube GT-NFF-AL](#)

URL: <https://www.polyphaser.com/type-n-surge-protector-6ghz-4ghz-gas-discharge-tube-gt-nff-al-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. PolyPhaser reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. PolyPhaser does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and PolyPhaser does not assume any liability arising out of the use of any part or documentation.

Type N F/F Bulkhead Coaxial RF Surge Protector, DC - 6GHz, 90W,  
IP67, 60 V Max., 5mJ, 20kA, Gas Discharge Tube

**GT-NFF-AL CAD Drawing**



ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY.

<p><b>PolyPhaser</b></p>		SHEET	1	of	1
		SCALE	1:1		
<p>TITLE</p>		<p>GAS TUBE NON-REPLACEABLE dc-6GHz 50-100W N FEM</p>			
SIZE	A	CAGE	30992	PROD CAT	RFP
		DRAWING NUMBER	GT-NFF-AL		
		REV	A		

UNLESS OTHERWISE SPECIFIED  
LEADING DIMENSIONS ARE IN INCHES  
DIMENSIONS IN [ ] ARE MILLIMETERS

TOLERANCES:  
FRACTIONS: ± 1/32 .XX± .01  
ANGLES: ± 1° .XXX± .005

THIRD-ANGLE PROJECTION

NOTED: THE INFORMATION AND DESIGN IN THIS DRAWING IS THE PROPERTY OF POLYPHASER CORP. ALL RIGHTS RESERVED.

**HARDWARE INCLUDED:**

QTY	DESCRIPTION
1	BRACKET MOUNTING AL 5052-H32
2	NUT 8-32 HEX 18-8 SS
2	WASHER #8 410 SS INTERNAL
2	SCREW 8-32x.50 PHIL MS PAN 18-8 SS
1	O-RING 016 SILICONE
1	NUT 5/8-24 303 HEX SS

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.